


## FUEL INJECTION NOZZLE

**Patent number:** JP10141183  
**Publication date:** 1998-05-26  
**Inventor:** RIYUU IKUTAMI  
**Applicant:** ISUZU MOTORS LTD  
**Classification:**  
- **international:** F02M61/18; F02M61/18; F02M61/06; F02M61/10  
- **european:** F02M61/16C2  
**Application number:** JP19960318493 19961115  
**Priority number(s):** JP19960318493 19961115

[Report a data error here](#)

### Abstract of JP10141183

**PROBLEM TO BE SOLVED:** To provide a fuel injection nozzle capable of providing a sufficient rotational flow in a fuel stay, making uniform a mixture between fuel and air and preventing the occurrence of soot. **SOLUTION:** Fuel supplied through spiral passages 13 and 14 formed between the wall surface 7 of the hollow hole 4 of a nozzle main body 2 and the sliding surface 8 of a needle valve 3 becomes a rotational flow in a fuel stay 15. Since the fuel stay 15 is a tapered annular chamber, the rotational flow is suddenly accelerated toward a single injection hole 5. Since the single injection hole 5 has a tapered surface 6 fan-shaped toward an injecting direction, the action of the fan-shaped nozzle forms a flow widened in a radial direction. The fuel has a large tangential direction speed when injected from the single injection hole 5 and dispersed more uniformly in a combustion chamber to become mist.



Data supplied from the esp@cenet database - Worldwide